

PRODUCT TECHNICAL DATA SHEET

Product name: Wood filler

Producer: DAKKO Dawid Koksa

Distribution: KARMEC AS

Salhusvegen 266, 5107 Salhus, Bergen

tlf. +47 984 53 017

e-mail: post@dakko.no

www.dakko.no

Description and application:

Wood putty is an acrylic sealing and filling compound for wood and wood-like products. It is used to fill small cavities and gaps. It is intended for use both outdoors and indoors.

Features/advantages:

- ready to use without additional preparation;
- ecological, water-soluble, free of organic solvents;
- safe to use, does not contain irritating ingredients;
- simple in application.

Technical data:

Color - 23 ready colors: white, larch, walnut, dark walnut, light beech, medium beech, dark beech, light pine, medium pine, dark pine, birch, ebony, rosewood, spruce, mahogany, ash, alder, light oak, medium oak, dark oak, gray, wenge, black, chestnut.

Number of layers: 1-3.

Thinning - not recommended.

Drying time - about 1mm/1.5h (at a temperature of 20 °C and air humidity of 60%), at lower temperatures and higher humidity the drying time may be longer, as well as with a thicker layer of the product.

Apply at temperatures from +5 °C to +25 °C.

Usage:

Substrate preparation: The substrate should be dry, free of dust and miscellaneous dirt.

Product preparation and application:

Wood filler is a ready-to-use product. After proper preparation of the substrate, you can proceed to filling the cavities. The product is applied with a spatula.

Tools:

- stainless steel spatula.

After finishing work, wash the tool with warm water.

Additional information:

Protect the product against sunlight and freezing. Store in tightly closed containers at temperatures from +5°C to +25°C. Do not mix with other products.

Detailed information is given in the product data sheet.

Expiry date: 24 months in tightly closed packaging.

Available packages:

- 0,3 kg,

- 1kg,

- 5kg,

- 10kg,